

**AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions and listings of claims in the application:

**LISTING OF CLAIMS:**

1.-14. (canceled).

15. (currently amended): ~~The method according to claim 1,~~ A method of downloading  
re-programming data from a network for installation in a radio transmitter/receiver comprising:  
receiving communication from a first dedicated channel; and  
broadcasting, on the first dedicated channel, at least the frequency and radio access  
parameters of a second channel from which re-programming data is downloaded,  
wherein the radio access parameters comprise parameters indicative of communication  
standards supported by the network,  
wherein a bandwidth of the first dedicated channel is narrower than the bandwidth of the  
second channel,  
wherein the first dedicated channel is a pilot channel that is a channel separate from a  
traffic channel and a control channel, and  
wherein the second channel is a bootstrap channel comprising:  
a first sub-channel; and  
a second sub-channel,

wherein the re-programming data is downloaded via the first sub-channel, and a signal control for error reduction during communication is performed via the second sub-channel.

16. <sup>2</sup> (currently amended): ~~The method according to claim 8,~~ A method for downloading re-programming data over-the-air from a network for installation in a radio transmitter/receiver, comprising :  
\_\_\_\_\_ providing a first channel for dedicated use and a second channel to download the re-programming data, a bandwidth of the first channel being narrower than the bandwidth of the second channel;  
broadcasting, on the first channel, at least frequency and radio access parameters of the second channel, wherein the radio access parameters comprise parameters indicative of communication standards supported by the network; and  
downloading the re-programming data to the radio transmitter/receiver on the second channel based on the broadcasted parameters,  
wherein the first channel is a pilot channel that is a channel separate from a traffic channel and a control channel, and

wherein the second channel is a bootstrap channel comprising:

a first sub-channel; and

a second sub-channel,

wherein the re-programming data is downloaded via the first sub-channel, and a signal control for error reduction during communication is performed via the second sub-channel.

17. (currently amended): ~~The method according to claim 1,~~ A method of downloading  
re-programming data from a network for installation in a radio transmitter/receiver comprising:  
receiving communication from a first dedicated channel;  
broadcasting, on the first dedicated channel, at least the frequency and radio access  
parameters of a second channel from which re-programming data is downloaded,  
wherein the radio access parameters comprise parameters indicative of communication  
standards supported by the network,  
wherein a bandwidth of the first dedicated channel is narrower than the bandwidth of the  
second channel, and  
wherein the first dedicated channel is a pilot channel that is a channel separate from a  
traffic channel and a control channel;  
the method further comprising:  
checking if a programming of the radio transmitter/receiver is compliant with the  
parameters indicative of the communication standards supported by the network;  
if the programming of the radio transmitter/receiver is not compliant with the parameters  
indicative of the communication standards supported by the network, terminating processing of  
the radio transmitter/receiver; and  
if the programming of the radio transmitter/receiver is compliant with the parameters  
indicative of the communication standards supported by the network, establishing  
communication between the radio transmitter/receiver and the network on the second channel.

18. (currently amended): The method according to claim 17, further comprising:

if the programming of the radio transmitter/receiver is compliant with the parameters indicative of the communication standards supported by the network, determining if a communication change has been requested;

if the communication change has not been requested, releasing communication on the second channel; and

if the communication change has been requested, performing the requested communication change.

19. (previously presented): The method according to claim 18,



wherein the performing of the requested communication change comprises:

maintaining communication between the radio transmitter/receiver and the network on the second channel;

determining if the radio transmitter/receiver is configured to support the requested communication change;

if the radio transmitter/receiver is not configured to support the requested communication change, reconfiguring the radio transmitter/receiver to support the requested communication change; and

downloading to the transmitter/receiver, on the second channel, the re-programming data for performing the requested communication change.

 20. (previously presented): The method according to claim  19, wherein the reconfiguring of the radio transmitter/receiver comprises downloading to the radio transmitter/receiver, on the second channel, a scheme/protocol required to support the requested communication change.